


## NPN General Purpose Amplifier

**SOT-23**

### Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- High Conductance
- Part no. with suffix "Q" means AEC-Q101 qualified

### Applications

- Switching and linear amplification

### Mechanical Data

- **Case:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** 2X

### ■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Value
Collector-Base Voltage	$V_{CBO}$	V	60
Collector-Emitter Voltage	$V_{CEO}$	V	40
Emitter-Base Voltage	$V_{EBO}$	V	6
Collector Current -Continuous	$I_C$	mA	600
Total Device Dissipation (*)	$P_D$	mW	300
Thermal Resistance From Junction To Ambient (*)	$R_{\theta JA}$	°C/W	417
Junction Temperature	$T_J$	°C	-55 to +150
Storage Temperature	$T_{STG}$	°C	-55 to +150

(\*) Device mounted on FR-4 PCB 1.0 x 1.0 x 0.06 inch.



## ■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	$I_C=10mA, I_E=0$	60	-
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	$I_C=1mA, I_B=0$	40	-
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	$I_E=100\mu A, I_C=0$	6	-
Collector cut-off current	$I_{CEO}$	nA	$V_{CE}=35V, I_B=0$	-	100
Base cut-off current	$I_{CBO}$	nA	$V_{CB}=60V, I_E=0$	-	100
Emitter cut-off current	$I_{EBO}$	nA	$V_{EB}=3V, I_C=0$	-	100
DC current gain	$h_{FE}$		$V_{CE}=1V, I_C=150mA$	100	300
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C=150mA, I_B=15mA$	-	0.4
Base-emitter saturation voltage	$V_{BE(sat)}$	V	$I_C=150mA, I_B=15mA$	-	0.95
Transition frequency	$f_T$	MHz	$V_{CE}=10V, I_C=20mA, f=100MHz$	250	-
Delay time	$t_d$	ns	$V_{CC}=30V, V_{BE(off)}=0.2V$ $I_C=150mA, I_{B1}=15mA$	-	15
Rise time	$t_r$	ns		-	20
Storage time	$t_s$	ns	$V_{CC}=30V, I_C=150mA, I_{B1}=I_{B2}=15mA$	-	225
Fall time	$t_f$	ns		-	30

## ■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBT4401Q	F2	Approximate 0.01	3000	30000	120000	7" reel

## ■ Characteristics (Typical)







Fig. 3 - Collect-Emmitter Saturation Voltage




Fig. 4 - Base-Emmitter Voltage




Fig. 5 - Base-Emmitter On Voltage




Fig. 6 - Cob/Cib— $V_{CB}/V_{EB}$




Fig. 7 - Safe Operating Area






Fig. 8 - Collector Power Derating Curve




## ■ SOT-23 Package Outline Dimensions



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.035	0.045	0.90	1.15	
A1	0.000	0.004	0.00	0.10	
A2	0.035	0.041	0.90	1.05	
b	0.012	0.020	0.30	0.50	
c	0.004	0.008	0.10	0.20	
D	0.110	0.118	2.80	3.00	
E	0.047	0.055	1.20	1.40	
E1	0.089	0.100	2.25	2.55	
e	0.370TYP		0.95TYP		
e1	0.071	0.079	1.80	2.00	
L	0.220REF		0.55REF		
L1	0.012	0.020	0.30	0.50	
θ	0°	8°	0°	8°	

## ■ SOT-23 Suggested Pad Layout



Unit:  $\frac{\text{inch}}{\text{mm}}$



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.